

KENTWOOD™ Product Profile

KOMBO

Value-Priced Thermo-Acoustic Underlay

Kentwood Kombo offers a three-in-one underlay at a value-conscious price: it's a floating floor underlay, a vapor barrier and acoustic underlay all in one easy to install product. Kombo features a top layer of high density polyethylene foam with an integral foil vapor barrier, and delivers excellent acoustic insulating performance with an FIIC rating of 58. Kombo is for use in floating floor installations over concrete or plywood subfloors and can be used on, above or below grade. It's also approved for use over radiant heat.

FEATURES INCLUDE:

- superior soundproofing performance (FIIC 58, ASTC 55)*
- helps correct minor subfloor irregularities
- integral foil membrane inhibits vapor transfer and heat loss
- high density cross-linked foam construction
- easy to install, cuts with scissors

INSTALLATION OPTIONS:



Above grade – Yes
On grade – Yes
Below grade – Yes



Yes



No



Yes



Yes



SPECIFICATIONS:

FIIC Rating: 58
ASTC Rating: 55
Thickness: 2 mm
Width: Approx 44" (1150mm)
Length: Approx 80 feet (24.24m)
Coverage, per roll: 300 sq/ft (27.88 sq/m)
Weight, per roll: 13.6 lbs (6.2 kg)
SKU #: 19205

***Product tested in combination with 7½" (190mm) concrete slab. For more information on FIIC & ASTC Ratings for this product, please contact your KENTWOOD™ representative.**

For more images and product information please visit www.kentwoodfloors.com

KENTWOOD™ floors are made from real wood, not a manufactured imitation, so every piece of KENTWOOD™ flooring will have a unique appearance. Showroom samples and photographic reproductions may not be representative of the full range of color, texture and grain variations which can occur in the product itself. Product selection and all product specifications are subject to change without notice. The trade-marks KENTWOOD™ and THE KENTWOOD COLLECTION™ are owned by Kentwood Floors Inc. and are used under license.

Rev 2008-07-31