

IMPORTANT NOTICE – PLEASE READ

The following chart lists recommended fasteners for nail down installation of Kentwood floors, along with recommended spacing. Due to the wide variety of different wood species, surface treatments, construction methods and milling specifications used in Kentwood floors, products that appear to be the same or similar may require different installation methods for best results. Please consult the chart carefully to ensure you are using a fastener and spacing schedule specifically recommended for the product you are installing. The chart also indicates where glue assisted procedures are required or recommended.

Factors such as age and wear may affect the performance of any nailer. Regularly maintain your equipment and replace worn or damaged components for optimum performance.

Prior to beginning any installation, installers are advised to test nail a piece of flooring to ensure the nailer / fastener combination will provide satisfactory results with the flooring product being installed. For complete installation instructions please visit kentwoodfloors.com

COUTURE	Fastener	Gauge	Size	Nail Spacing	Distance from end	Comments
Natural Oiled 20mm [3/4"] thick	Staple	15 1/2	2"	4 - 6"	1 - 2"	Recommended installation is glue down. If nailing, glue assist with elastomeric flooring adhesive and glue end joints with non-crystallizing floating floor adhesive. For more information on glue assist techniques, contact Kentwood Technical Services.
	Cleat	16	2"	4 - 6"	1 - 2"	
Engineered Strip 10mm [3/8"] thick	Cleat	18	1 1/2 - 1 3/4"	4 - 6"	1 - 2"	
Fantasy 15mm [5/8"] thick	Staple	15 1/2	2"	4 - 6"	1 - 2"	
	Cleat	16	2"	4 - 6"	1 - 2"	

ORIGINALS	Fastener	Gauge	Size	Nail Spacing	Distance from end	Comments
European Plank 15mm [5/8"] thick	Staple	15 1/2	2"	4 - 6"	1 - 2"	Recommended installation is glue down or floating. If nailing, glue assist with elastomeric flooring adhesive and glue end joints with non-crystallizing floating floor adhesive. For more information on glue assist techniques, contact Kentwood Technical Services.
	Cleat	16	2"	4 - 6"	1 - 2"	
Antiqued Solid 18mm [3/4"] thick	Staple	15 1/2	2"	6 - 8"	2 - 3"	
	Cleat	16	2"	6 - 8"	2 - 3"	
Antiqued Engineered 14 - 14.2mm [9/16"] thick	Cleat	18	1 3/4"	4 - 6"	1 - 2"	
		16	1 3/4 - 2"	4 - 6"	1 - 2"	
Engineered 13.5mm [1/2"] thick	Cleat	18	1 3/4"	4 - 6"	1 - 2"	
		16	1 3/4 - 2"	4 - 6"	1 - 2"	
Solid Hardwood 18mm [3/4"] thick	Staple	15 1/2	2"	6 - 8"	2 - 3"	
	Cleat	16	2"	6 - 8"	2 - 3"	
Urban Collection 12mm [1/2"] thick	Cleat	18	1 3/4"	4 - 6"	1 - 2"	
Milltown 12mm [1/2"] thick	Cleat	18	1 3/4"	4 - 6"	1 - 2"	

