

PRODUCT PROFILE

KOMBO

Value-Priced Thermo-Acoustic Underlay




Kentwood Kombo offers a three-in-one underlay at a value-conscious price: it's a floating floor underlay, a vapor retarder and acoustic underlay all in one easy to install product. Kombo features a top layer of high density polyethylene foam with an integral foil vapor retarder, and delivers excellent acoustic insulating performance with an FIIC rating of 58. Kombo is for use in floating floor installations over concrete or plywood subfloors and can be used on, above or below grade. It's also approved for use over

radiant heat. Kombo is a class III- permeable underlay with a perm rating of 2.18. In certain circumstances like on grade or below grade installations, additional vapor barrier, class I non-permeable, with perm rate of less than 0.15 may be required. For further details please refer to NWFA guidelines.



Product Features

- Superior soundproofing performance (FIIC 58, ASTC 56)*
- Helps correct minor subfloor irregularities
- Integral foil membrane inhibits vapor transfer and heat loss
- High density cross-linked foam construction
- Easy to install, cuts with scissors

Installation Options



Above grade: **OK**
On grade: **OK**
Below grade: **OK**



Product Specifications

FIIC Rating: **58**

ASTC Rating: **55**

Thickness: **2 mm**

Width: **Approx 44" (1150mm)**

Length: **Approx 80 feet (24.24m)**

Coverage (per roll): **300 sq/ft (27.88 sq/m)**

Weight (per roll): **13.6 lbs (6.2 kg)**

SKU #: **19205**

*Product tested in combination with 7½" (190mm) concrete slab. For more information on FIIC & ASTC Ratings for this product, please contact your KENTWOOD™ representative.